


**CLAMPING HEADS FOR SINGLE-SPINDLE
TÊTES DE SERRAGE POUR MONOBROCHES
SPANNKÖPFE FÜR EINSPINDLER**



A = Alésage / Ausführung der Bohrung / Bore			
L	lisse	glatt	smooth
R	rainures circulaires	mit Querrillen	with radial grooves
S	striée	mit Längs- und Querrillen	with radial and longitudinal grooves
W	pince douce	weich/ausdrehbar	emergency collet

Type/Typ	Ref./Art.	L	D	●	A	●	A	■	A
32	32L	44	57,7	3-32	L	7-27	L	7-22	L
	32R	44	57,7	8-32	R	8-27	R	8-22	R
	32S	44	57,7	11-32	S				
	32EM	44	57,7	3-32	W				

Type/Typ	Ref./Art.	L	Ref./Art.	L	D	●	A	●	A	■	A
42	42L	42	42BL	47	79,3	3-42	L	7-36	L	7-30	L
	42R	42	42BR	47	79,3	8-42	R	8-36	R	8-30	R
	42S	42	42BS	47	79,3	11-42	S				
	42EM	42			79,3	3-42	W				

pour Index MS 42 on peut utiliser la réf. 42B / for Index MS 42 it can be used 42B / für Index MS 42 kann man die Ref. 42B benutzen

Type/Typ	Ref./Art.	L	D	●	A	●	A	■	A
52	52L	46	79,3	3-52	L	7-9	L	7-9	L
	52R	46	79,3	8-52	R	10-45	R	10-36	R
	52S	46	79,3	11-52	S				
	52EM	46	79,3	3-52	W				

Type/Typ	Ref./Art.	L	Ref./Art.	L	D	●	A	●	A	■	A
65	65L	53	65BL	58	99,5	3-65	L	7-9	L	7-9	L
	65R	53	65BR	58	99,5	8-65	R	10-42	R	10-42	R
	65S	53	65BS	58	99,5	11-65	S	43-56		43-46	
	65EM	53			99,5	3-65	W				

pour Index MS 52 on peut utiliser la réf. 65B / for Index MS 52 it can be used 65B / für Index MS 52 kann man die Ref. 65B benutzen

Type/Typ	Ref./Art.	L	D	●	A	●	A	■	A
80	80L	53	114,5	4-80	L	7-68	L	7-56	L
	80R	53	114,5	8-80	R	8-68	R	8-56	R
	80S	53	114,5	11-80	S				
	80EM	53	114,5	4-80	W				

dimensions in mm / dimensions en mm / Maße in mm

Cap. of tightening / cap. de serrage / Spannkapazität: +/- 0.30

www.dttechnologies.eu